

NCT6 Series

Modle	NCT6-300	NCT6-400	NCT6-500	NCT6-600	NCT6-700	NCT6-800	NCT6-900	NCT6-1000
Width of Material (mm)	300	400	500	600	700	800	900	1000
Thickness of Material (mm)	1.0 ~ 6.0							
Feed Roll (mm)	114 x 2 pcs			132 x 2 pcs			144 x 2 pcs	
Work Roll (mm)	96 x 12 pcs	96 x 12 pcs	96 x 12 pcs	114 x 12 pcs	114 x 12 pcs	114 x 12 pcs	120 x 12 pcs	120 x 12 pcs
Work Roll Arrangement	First Section:Upper 1 / Lower 2, Second Section:Upper 5 / Lower 4							
Main Servo Motor (kW)	5.0	5.0	7.0	7.0	7.0	11.0	15.0	15.0
Air Supply (kg/cm2)	5							
P.L.H Adjustment (mm)	Cust. Demand High \pm 100							

Uncoiler

Width of Material (mm)	300	400	500	600	700	800	900	1000
Max. Coil Weight (kg)	1500	2000	2000	3000	3000	5000	5000	5000
Coil I.D. (mm)	Ø450 ~ 520				Ø480 ~ 520			
Max. Coil O.D. (mm)	1200 or 1500							
Uncoiler Expansion	Hydraulic							
Uncoiler Motor (HP)	1	2	2	3	3	5	5	5
Uncoiler Inverter (kW)	1.5	2.2	2.2	3.7	3.7	3.7	5.5	5.5